

# 02.15 RC/N6 roll cage

Optimised for transport on the loading area of trucks

> With integrated moving aid

> Fully closed



RC/N6 Basic model with attachable wire shelf (standard)



Can be nested to save space

Space requirement in row  
 per roll cage 400 mm  
 10 roll cages 4,355 mm  
 50 roll cages 20,355 mm

### Moving aid

The integrated rail for foot leverage or forklift guidance supports manoeuvring over steps and through doorways.



**Standard equipment:** chassis made of square tube frame, curved. Hinged support surface made of square tube frame with wire, strengthened with reinforcing strips. Container structure, made of round tube frame with wire mesh and metal hinges. Door leaf opening angle 270°.

**Castors:** 4 swivel castors, including 2 with brake. Elastic tread, grey.

**Surface finish:** high gloss, galvanised, chrome-plated.

		RC/N6
<b>Order no.</b>		06.05 877.50
A, length (mm)		1,180
B, width (mm)		755
C, height (mm)		1,980
D, loading height (mm)		1,720
Mesh size (mm)		50 x 50
Castor Ø (mm)		125
Total load capacity / per shelf (kg)		500 / 75
Weight (kg)		100
<b>Accessories</b>		
<b>Wire shelf (optional)</b>		00.52 930.50