

# 02.07 RC/S9 roll cages

Optimised loading area for transport in trucks

> Fully closed

> Basis for many customer-specific variants



RC/S9 Basic model with height of 1925 mm and wire shelf (accessories)

## Locking

**Latching 3-point locking element** for security during transport.

The locking mechanism can be secured with a padlock if required.



## Brake mechanism

Two swivel castors are equipped with brakes.



**Standard equipment:** metal chassis. Square tube frame with wire support surface, strengthened with reinforcing strips. Container structure made of square tube frame with wire mesh, riveted. Door with metal hinges. Opening angle 270°.

**Castors:** 4 swivel castors made of polyamide, 2 with brakes.

**Surface finish:** high gloss, galvanised, chrome-plated.

	RC/S9	RC/S9
<b>Order no.</b>	06.13 221.50	06.13 223.50
A x B x C, length x width x height (mm)	1,205 x 810 x <b>1,660</b>	1,205 x 810 x <b>1,905</b>
D, loading height (mm)	1,460	1,705
Mesh size (mm)	50 x 50	50 x 50
Castor Ø (mm)	125	125
Total load capacity / per shelf (kg)	500 / 75	500 / 75
Weight (kg)	65	74
<b>Accessories</b>		
<b>Wire shelf</b>	28.01 525.50	28.01 525.50
<b>Wire shelf, with raised edge on one side</b>	28.01 526.50	28.01 526.50
<b>Wooden shelf</b>	00.84 684.95	00.84 684.95