

02.04 RC/S9 roll cages

Optimised loading platform for truck transport

- > Fully closed
- > Locking mechanism
- > With optional wooden shelf



RC/S9 Equipment example with height of 1,925 mm

Locking mechanism

Latching 3-point locking element for security during transport.

The locking mechanism can be secured with a padlock if required.



Brake (optional)

Swivel castor set with 2 brakes for a secure position.



Standard equipment: Metal chassis. Square tube frame with wire support surface, strengthened with reinforcing strips. Container structure made of square tube frame with wire mesh, riveted. Door with metal hinges. Opening angle 270°.

Castors: 4 swivel castors made of polyamide

Surface finish: High-gloss galvanised, chrome-plated.

	RC/S9	RC/S9
Order no.	06.13 221.50	06.13 223.50
A x B x C, length x width x height (mm)	1,205 x 810 x 1,660	1,205 x 810 x 1,925
D, loading height (mm)	1,460	1,705
Mesh size (mm)	50 x 50	50 x 50
Castors Ø (mm)	125	125
Total load capacity / per shelf (kg)	500 / 75	500 / 75
Weight (kg)	65	74
Accessories		
Wire shelf	28.01 525.50	28.01 525.50
Wire shelf, with raised edge on one side	28.01 526.50	28.01 526.50
Wooden shelf	00.84 684.95	00.84 684.95